

VIP Swing

HodgePodge


















Published: May 2023

VIP Swing Product Specification

HodgePodge Playpoints are climbers or rockers or twisters. They are Playpoints first and foremost, but they are also very nice pieces of public design, and they are sculptural. All HodgePodge Playpoints are high-end engineered units made from high-quality materials like stainless steel with a brushed finish, powder coated recycled aluminum connectors, high density polyethylene (HDPE) panels and ITR-bearings for maximum safety and durability.

The VIP Swing is a pendulum swing for two users giving each other a "kick" without direct contact.

97.100.026

	Product Family	HodgePodge
	Length x Width x Height (m) Length x Width x Height ("")	4,7 x 2,0 x 3,5 15-4 x 6-7 x 11-6
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ("")	7,7 x 9,2 8,4 x 9,8 27-5 x 32-2
	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ("")	2,2 10-8
	Age	5
	Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	53,6 673,8
	Number of Foundations	2
	Concrete Volume C20/C25 (m³) Concrete Volume C20/C25 (ft³)	1,4 50
	Number of skilled Installers required	2
	Installation Time without Foundation	3 hours
	Dimensions of largest Part (m) Dimensions of largest Part ("")	4,5 x 0,1 x 0,1 0-4 x 14-9
	Weight of heaviest Part (kg) Weight of heaviest Part (lbs)	175 385
	Shipping Volume (m³) Shipping Volume (ft³)	1,8 63,6
	Total Weight (kg) Total Weight (lbs)	565 1250
	Spare Part Guarantee	Lifelong

The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.

Technical Data

Technical changes are reserved.
The following text can also be used for tenders.

Posts:

Steel pipes Ø 133 mm (5 1/4"), wall thickness 10 mm (3/8") with a round cast aluminum post top. Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process.

Terranos®- Clamps:

Two-part cast aluminum connecting clamps for the height-adjustable connection of rope elements or steel pipes to Terranos®- steel posts. Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process.

Ropes:

U-Rope®-round strand ropes with galvanized and covered wires. External strands with non-abrasive UV-resistant polyester-yarn (no polypropylene), Ø 16 mm (5/8").

Spreader bar:

Frameworkx®- stainless steel tubes Ø 60,3 mm (2 3/8"), smoothed and brushed/ polished.

Tubes:

Frameworkx®- steel tubes, Ø 60,3 mm (2 3/8"). Anti-corrosion treatment and color finish: sandblasting, sensimir galvanised and solvent-free epoxy-/ polyester-process.

Spheres:

Frameworkx®- aluminum ball connectors, Ø 200 mm (7 7/8"). Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process. With embedded fastening system. Securely closed with durable EPDM-caps.

Pendulum Seats:

Round rubber seat on sheathed stainless steel chain which is connected rotatable to a Frameworkx®- aluminum ball connector. Connected to the posts by 4 bracing ropes at Frameworkx®- aluminum ball connectors with swivel joints.

