

Bowl Swing

HodgePodge


















Published: August 2023

Bowl Swing Product Specification

HodgePodge Playpoints are climbers or rockers or twisters. They are Playpoints first and foremost, but they are also very nice pieces of public design, and they are sculptural. All HodgePodge Playpoints are high-end engineered units made from high-quality materials like stainless steel with a brushed finish, powder coated recycled aluminium connectors, high density polyethylene (HDPE) panels and ITRbearings for maximum safety and durability.

Thanks to its low access height the Bowl Swing, just like the Cup Swing, is perfectly suited for toddlers or children with limited mobility.

90.260.532

	Product Family	HodgePodge
	Length × Width × Height (m) Length × Width × Height ("")	1,3 × 3,7 × 2,9 4-2 × 11-10 × 9-3
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ("")	6,8 × 3,7 7,0 × 7,3 22-11 × 23-11
	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ("")	1,18 5-9
	Age	3
	Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	24,3 388,4
	Number of Foundations	2
	Concrete Volume C20/C25 (m³) Concrete Volume C20/C25 (ft³)	1,2 42,5
	Number of skilled Installers required	2
	Installation Time without Foundation	2 hours
	Dimensions of largest Part (m) Dimensions of largest Part ("")	2,3 × 0,3 × 0,2 7-7 × 1-0 × 0-8
	Weight of heaviest Part (kg) Weight of heaviest Part (lbs)	55 121,3
	Shipping Volume (m³) Shipping Volume (ft³)	2,6 91,8
	Total Weight (kg) Total Weight (lbs)	380 837,8
	Spare Part Guarantee	Lifelong

The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.

Technical Data

Technical changes are reserved.
The following text can also be used for tenders.

Posts:

Steel pipes Ø 133 mm (5 1/4"), wall thickness 6,3 mm (1/4") with a round cast aluminum post top. Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process.

Spheres:


Framework®- aluminum ball connectors, Ø 250 mm (9 13/16"). Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process. With embedded fastening system. Securely closed with durable EPDM-caps.

Nest Swing Seat:

Ø 1200 mm (3'-11 1/4"). Galvanized steel ring covered with shock-absorbing material and wrapped with rope. Tight-knit net made of rope Ø 16 mm (5/8") is hung into the ring.

Suspension:

U-Rope®-round strand ropes with galvanized and covered wires. External strands with non-abrasive UV-resistant polyester-yarn (no polypropylene), Ø 16 mm (5/8"). Connected to the joint with stainless steel chains.



1:200