Cosmo S Base - Product Specification



Cosmo - The first totally round rope play structure

The innovative space structure offers exciting play options never before experienced. Cosmo is a whole new round of fun in play equipment: The first totally round rope play structure has arrived.

Apart from the basic system, Cosmo stands out due to its many freely selectable add-ons and diverse play activities. This gives the Cosmo an advantage over several rounds compared to conventional climbing frames.

In 2008 Cosmo received the prestigious "Red Dot" design award for excellent design quality.

Cosmo S Base -At a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487: Cosmo 90.111.000 3+ 1.83 m (6'-0")

1.83 m (6'-0") 3.4 m x 3.2 m x 2.9 m (11'-0" x 10'-7" x 9'-6") 7.0 m x 7.0 m

7.0 m x 7.0 m (23'-0" x 23'-0")

36.0 m² 38.5 m² (414.4 sf) Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required: Installation Time without foundation:

Weight of heaviest part: Shipping Volume: Spare part guarantee:

Revision: March 2016

Dimensions of largest part:

Certificate according to DIN EN 1176:

3 pc.

0.4 m³ (14.1 ft³)

3

6 hours

1.2 m x 0.8 m x 1.0 m (3'-11" x 2'-7" x 3'-4")

110 kg (242.5 lbs) 2.3 m³ (81.2 ft³)

Lifelong

No.: Z2 15 12 10256 245 TÜV Product Service




Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607


T + 1 864 627 1092 F + 1 864 627 1178

www.berliner-playequipment.com info@berliner-seilfabrik.com

Page 1

Cosmo S Base - Product Specification





Technical Data.

The following text can also be used for tenders.

Tube framework:

Curved stainless steel tubes; Ø 60.3 mm (2 3/8")

Nodes

Frameworx-aluminum ball connectors; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; incorporating an ASTEM TT net tensioning system; securely closed with durable EPDM- caps

Ropes

Revision: March 2016

U-Rope®-round strand ropes with galvanized and covered wires; external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene): Ø 16 mm (5/8")

Spacial netting:

Rope crossing points are localized with durable, forged aluminum-alloy cloverleaf rings and forged aluminum-alloy ballknots (no plastic connections); in situ-replaceable rope strands (no special tools required)





Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178