Cosmo.10 - Product Specification



Cosmo - The first totally round rope play structure

The innovative space structure offers exciting play options never before experienced. Cosmo is a whole new round of fun in play equipment: The first totally round rope play structure has arrived.

Apart from the basic system, Cosmo stands out due to its many freely selectable add-ons and diverse play activities. This gives the Cosmo an advantage over several rounds compared to conventional climbing frames.

In 2008 Cosmo received the prestigious "Red Dot" design award for excellent design quality.

Cosmo.10 -At a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required ASTM 1487:

Minimum space required DIN EN 1176:

Cosmo 90.112.100 2.30 m (7'-7") 8.4 m x 6.0 m x 3.8 m

(27'-5" x 19'-9" x 12'-4") 12.2 m x 9.7 m 12.2 m x 10.0 m (40'-0" x 32'-8")

78.8 m²

76.9 m² (827.7 sf)

Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required: Installation Time without foundation: Dimensions of largest part:

Weight of heaviest part: Shipping Volume: Spare part guarantee:

Revision: March 2016

5 pc.

1.5 m³ (53.0 ft³)

7 hours

0.1 m x 1.3 m x 4.6 m (0'-4" x 4'-3" x 15'-1")

105 kg (231.5 lbs) 4.0 m³ (141.3 ft³)


Lifelong




Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 18646271178

Cosmo. 10 - Product Specification





Technical Data.

The following text can also be used for tenders.

- Cosmo
- Banister
- Duck Jibe

Tube framework:

Curved stainless steel tubes; Ø 60.3 mm (2 3/8")

Nodes:

Frameworx-aluminum ball connectors; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; incorporating an ASTEM TT net tensioning system; securely closed with durable EPDM- caps

Ropes

U-Rope®-round strand ropes with galvanized and covered wires; external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene): Ø 16 mm (5/8")

Spacial netting:

Rope crossing points are localized with durable, forged aluminum-alloy cloverleaf rings and forged aluminum-alloy ballknots (no plastic connections); in situreplaceable rope strands (no special tools required)

Duck Jibe

Curved Frameworx stainless steel pipes Ø 60.3 mm (2 3/8"), wall thickness 2.9 mm; lubricated, antifriction reciprocal bearings; connected to the main Cosmo framework with a thick-walled Frameworx-aluminum ball connector, Ø 250mm (9-13/16"), standing platform is comprised of grained HDPE, 19 mm thick; the turning bearing construction located in the ground consists of Frameworx stainless steel pipe retainers, Ø 40 mm (1-3/5"), wall thickness 5 mm (3/16")

Curved banister:

Curved stainless steel pipes; Ø 60.3 mm (2 3/8") wall thickness 2.9 mm; connected to the main structure with 2 aluminum ball connectors Ø 200mm (7-9/10")



Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178



Revision: March 2016