Spaceball L.03 - Product Specification



Univers - Classics among rope playground equipment

Net structures offer hours of fun and adventure on several levels – climbing and swinging, up and down, horizontally and vertically – space on earth.

The original spatial nets: Born over 40 years ago as a play concept, continuously further developed in form and detail, still popular even after several generations.

Please note: Product specification refers to structure with standard foundation and stainless steel slide.

Spaceball L.03 – at a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487:

Univers 90.136.071 5+ 1.85 m (6'-1") 9.3 m x 7.1 m x 4.5 m (30'-5" x 23'-3" x 14'-9") 12.5 m x 10.5 m

12.5 m x 10.5 m 13.4 m x 10.7 m (43'-10" x 35'-3")

79.9 m² 89.8 m² (966.4 sf) Number of Foundations: Concrete Volume C20/C25:

Number of skilled installers required: Installation Time without foundation: Dimensions of largest part:

Weight of heaviest part: Shipping Volume: Spare part guarantee:

Revision: March 2016

Certificate according to DIN EN 1176:

7 pc. 2.1 m³ (74.2 ft³)

3

8 hours 4.7 m x 0.7 m x 0.5 m

4.7 III x 0.7 III x 0.5 III (15'-6" x 2'-4" x 1'-8") 110 kg (242.8 lbs) Upon request Lifelong


No.: Z2 16 01 10256 246 TÜV Product Service




Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178

Spaceball L.03 - Product Specification





Technical Data.

The following text can also be used for tenders.

- Spaceball L
- Access net
- Stainless steel slide

Tube framework:

Frameworx-steel tubes, \emptyset 60.3 mm (2 3/8"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process

Nodes

Frameworx-aluminum ball connectors; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; incorporating an ASTEM TT net tensioning system; securely closed with durable EPDM- caps

Ropes:

U-Rope®-round strand ropes with galvanized and covered wires: external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene); rope-diameter Ø 16 mm (5/8")

Spacial netting:

Rope crossing points are localized with durable, forged aluminum-alloy cloverleaf rings and forged aluminum-alloy ballknots (no plastic connections); in situreplaceable rope strands (no special tools required)

Access net:

Revision: March 2016

Rope Ø 16mm (5/8"); mesh size minimum 250 x 250 mm (9-4/5"); rope crossing points localized by durable, drop forged aluminum ballknots (no plastic)

Straight box slide:

Straight box slide made of stainless steel; the cheeks are welded with stainless steel handrails; afterwards smoothed and polished





Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178