Eddie.04

HodgePodge

Published: April 2023

Eddie.04 Product Specification

HodgePodge Playpoints are climbers or rockers or twisters. They are Playpoints first and foremost, but they are also very nice pieces of public design, and they are sculptural. All HodgePodge Playpoints are high-end engineered units made from high-quality materials like stainless steel with a brushed finish, powder coated recycled aluminium connectors, high density polyethylene (HDPE) panels and ITR-bearings for maximum safety and durability. The Eddie.04 is another shorty, but it stands slanted and its stainless steel stem is curved. Very stylish! It offers a nice little spin for the youngsters.



Eddie.04

() () () () () () () () () () () () () (Product Family	HodgePodge
	$\label{eq:length} \begin{split} & \text{Length} \times \text{Width} \times \text{Height (m)} \\ & \text{Length} \times \text{Width} \times \text{Height ('-'')} \end{split}$	0,5 × 0,5 × 0,9 1-8 × 1-8 × 3-0
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ('-")	3,5 × 3,5 4,2 × 4,2 13-8 × 13-8
0 0 ↓	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ('-")	0,40 1-4
пП	Age	3
	Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	9,6 147,0
$\Diamond^{\diamondsuit} \diamond$	Number of Foundations	1
••••••••••••••••••••••••••••••••••••••	Concrete Volume C20/C25 (m³) Concrete Volume C20/C25 (ft³)	0,15 5,3
	Number of skilled Installers required	2
	Installation Time without Foundation	2 hours
		0,5 × 0,5 × 1,4 1-8 × 1-8 × 4-8
	Weight of heaviest Part (kg) Weight of heaviest Part (lbs)	60 133
	Shipping Volume (m³) Shipping Volume (ft³)	1,1 39
îîî	Total Weight (kg) Total Weight (lbs)	75 166
\bigcirc	Spare Part Guarantee	Lifelong



Technical Data

Technical changes are reserved. The following text can also be used for tenders.

Turntable:

Stainless steel plate Ø 494 mm (1'-8"), covered with HDPE panels.

Tube:

Frameworx[®]- stainless steel tube Ø 60,3 mm (2 3/8").

Sphere:

Frameworx[®]- aluminum ball connectors, Ø 200 mm (7 7/8"). Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process. The ball incorporates an embedded fastening system. Securely closed with durable EPDM-caps.


Stand:

Stainless steel swivel stand with fully encapsulated bearing.

Covering:

Antiskid HDPE panels, 19 mm (3/4"), bolted on the turntable.





1:100