

HodgePodge





Published: April 2023

Eddie.05

Product Specification

HodgePodge Playpoints are climbers or rockers or twisters. They are Playpoints first and foremost, but they are also very nice pieces of public design, and they are sculptural. All HodgePodge Playpoints are high-end engineered units made from high-quality materials like stainless steel with a brushed finish, powder coated recycled aluminium connectors, high density polyethylene (HDPE) panels and ITR-bearings for maximum safety and durability.

At a height of 2.3 metres, the newest member of the Eddie family surpasses itself and turns into a real eye-catcher in any pedestrian zone. The HDPE surface is now even more slip-proof. As usual, this Eddie also combines fun, style and coolness into a single place to play.



Eddie.05

90.260.105

70.200.103		
(A. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2.	Product Family	HodgePodge
	$\begin{aligned} & \text{Length} \times \text{Width} \times \text{Height (m)} \\ & \text{Length} \times \text{Width} \times \text{Height ('-")} \end{aligned}$	0,7 × 0,5 × 2,3 2-3 × 1-8 × 7-5
[]	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ('-")	3,5 × 3,5 4,2 × 4,2 13-8 × 13-8
000	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ('-")	0,40 1-4
	Age	5
	Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	9,6 147,0
$\Diamond^{\Diamond}\Diamond$	Number of Foundations	1
	Concrete Volume C20/C25 (m³) Concrete Volume C20/C25 (ft³)	0,5 17,7
.	Number of skilled Installers required	2
	Installation Time without Foundation	2 hours
K Z	Dimensions of largest Part (m) Dimensions of largest Part ('-")	0,5 × 0,5 × 2,3 1-8 ×1-8 × 7-7
	Weight of heaviest Part (kg) Weight of heaviest Part (lbs)	70 155
	Shipping Volume (m³) Shipping Volume (ft³)	1,1 39
	Total Weight (kg) Total Weight (lbs)	85 188
	Spare Part Guarantee	Lifelong





Technical changes are reserved.

The following text can also be used for tenders.

Turntable

Stainless steel plate Ø 494 mm (1'-8"), covered with HDPE panels.

Tube:

Frameworx®- stainless steel tube Ø 60,3 mm (2 3/8").

Sphere:

Frameworx®- aluminum ball connectors, Ø 200 mm (7 7/8"). Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process. The ball incorporates an embedded fastening system. Securely closed with durable EPDM-caps.

Stand:

Stainless steel swivel stand with fully encapsulated bearing.

Covering

Antiskid HDPE panels, 19 mm (3/4"), bolted on the turntable.



