





Double Swingo.2.2

Here are two Swingo.2.2 directly connected to each other. So that you can use different swing seat variants.





Double Swingo.2.2 - at a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487:

Playpoints 90.340.049 5+

1.3 m (4'-4") 1.8 m x 7.2 m x 2.5 m

(5'-11" x 23'-8" x 8'-3") 7.2 m x 7.2 m

8.0 m x 10.9 m (26'-3" x 35'-10")

51.5 m² 73.5 m² (792 ft²) **Number of Foundations:** Concrete Volume C20/C25: Number of skilled installers required:

Installation Time without foundation: Dimensions of largest part:

Weight of the heaviest part: Shipping Volume: **Shipping Weight:** Spare part guarantee:

6 pc.

0.9 m3 (32 ft3) 2

3 hours 3.2 m x 0.6 m x 0.1 m

(10'-6" x 2'-0" x 0'-4") 35 kg (85 lbs) 2.4 m³ (61 ft³) 270 kg (596 lbs) Lifelong

Technical Data.

The following text can also be used for tenders.

Framework:

Stainless steel tube bends Ø 60.3 mm (2 3/8"), connected to Frameworx®-aluminum ball connectors; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; securely closed with durable EPDM-caps

Swing seat:

Revision: May 2016

The black rubber safety swing seat is by stainless steel chains rotatably mounted to the cross tube mounted in maintenance free nylon bushes. Ask for different swing seat variants.



Berliner Seilfabrik GmbH & Co. Lengeder Straße 2/4 D-13407 Berlin

Tel. +49.(0)30.41 47 24-0 Fax +49.(0)30.41 47 24-33

info@berliner-seilfabrik.com www.berliner-seilfabrik.com



