Sculptura.02 - Product Specification





M 1:200



Terranos Sculptura-Sloping posts in the Terranos® netscape

Sculptura is the "sloping" addition to the otherwise straight Terranos range. A Sculptura element extends with three sloping Terranos posts across the diagonal of a 3 x 3 m (9'-10" x 9'-10") Terranos grid. The centre posts always slope in the opposite direction to the other two outer posts. The diagonal terminates with one straight Terranos post respectively.

At a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487:

Terranos & Terranova 95.180.020

1.24 m 4.5 m x 2.3 m x 2.8 m (14'-8" x 7'-6" x 8'-11") $7.5 \, \text{m} \, \text{x} \, 5.3 \, \text{m}$ 6.0 m x 8.2 m (19'-6" x 26'-8")

5+

30.0 m²

36.2 m² (389.7 sf)

Number of Foundations: Concrete Volume C20/C25:

Number of skilled installers required: Installation Time without foundation: Dimensions of largest part:

Weight of heaviest part: Shipping Volume: Spare part guarantee:

Certificate according to DIN EN 1176:

5 pc.

2 hours

 $0.1 \, \text{m} \, \text{x} \, 0.5 \, \text{m} \, \text{x} \, 4.1 \, \text{m}$ (0'-4" x 1'-8" x 13'-5") 95 kg (209.4 lbs)

2.6 m3 (91.8 ft3)

4.0 m³ (141.3 ft³) Lifelong

Z2 16 01 10256 255 **TÜV Product Service**

Technical Data.

The following text can also be used for tenders.

Steel pipes Ø 133 mm (5 1/4"); wall thickness 5 - 10 mm (3/16" - 3/8") with a round cast aluminum post top; anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process

U-Rope®-round strand ropes with galvanized and covered wires; external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene): Ø 18 mm (11/16")

Terranos clamps:

Two-part cast aluminum connecting clamps for the heightadjustable connection of rope elements or steel pipes to Terranos steel posts; anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process

Pipes:

Stainless steel pipe railings; Ø 60.3 mm (2 3/8"); wall thickness 3 mm; with aluminum end caps



Tel. +49.(0)30.41 47 24-0 Fax +49.(0)30.41 47 24-33

info@berliner-seilfabrik.com



Revision: April 2016 www.berliner-seilfabrik.com Page 1