

## Swingo.2.4 - at a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487: Playpoints 90.260.504 3+ 1.7 m (5'-7") 5.9 m x 2.5 m x 3.4 m (19'-5" x 8'-3" x 11'-2") 8.9 m x 3.7 m 11.6 m x 9.6 m (38'-1" x 31'-6") 32.2 m<sup>2</sup> 66.9 m<sup>2</sup> (721 ft<sup>2</sup>) Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required: Installation Time without foundation: Dimensions of largest part:

Weight of the heaviest part: Shipping Volume: Shipping Weight: Spare part guarantee: Certificate according to DIN EN 1176: 6 pc. 0.9 m<sup>3</sup> (32 ft<sup>3</sup>) 2 2 hours

2 hours 3.8 m x 1.2 m x 0.1 m (12'-6" x 4'-0" x 0'-4") 35 kg (78 lbs) 1.7 m<sup>3</sup> (61 ft<sup>3</sup>) 185 kg (408 lbs) Lifelong No.: Z2 15 06 10256 231 TÜV Product Service

## Technical Data.

The following text can also be used for tenders.

## Framework:

Stainless steel tube bends Ø 60.3 mm (2 3/8"), connected to Frameworx®-aluminum ball connectors; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; securely closed with durable EPDM-caps



The black rubber safety swing seat is by stainless steel chains rotatable mounted to the cross tube mounted in maintenance free nylon bushes



Berliner Seilfabrik GmbH & Co. Lengeder Straße 2/4 D-13407 Berlin

Tel. +49.(0)30.41 47 24-0 Fax +49.(0)30.41 47 24-33

info@berliner-seilfabrik.com www.berliner-seilfabrik.com

## \*A