

Calisthenics.02

HodgePodge



Published: September 2024










Calisthenics.02 Product Specification

HodgePodge is a clever and versatile combination of play equipment and climbing structures that can be used anywhere and for numerous activities. A calisthenics system for sport activity, climbing trees, Wasps' nest, zip lines, swings and carousels for fun and excitement.

Calisthenics.02 combines climbing and calisthenics in one. Whether pull-ups or hand-overhand moves, fitness fans will be spoiled for choice when using this piece of apparatus, which is more than 9 metres long. Calisthenics.02 is just one of many possible variants: the color, shape and functionality can be tailored to specific requirements so as to fit in with the surroundings, whether urban or natural.

Calisthenics.02

95.190.481

	Product Family	HodgePodge
	Length × Width × Height (m) Length × Width × Height ("-")	9,0 × 3,2 × 2,4 29-4 × 10-5 × 7-10
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ("-")	* * *
	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ("-")	* *
	Age	*
	Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	* *
	Number of Foundations	4
	Concrete Volume C20/C25 (m³) Concrete Volume C20/C25 (ft³)	4,2 148,4
	Number of skilled Installers required	3
	Installation Time without Foundation	12 hours
	Dimensions of largest Part (m) Dimensions of largest Part ("-")	1,5 × 2,1 × 0,4 4-9 × 6-8 × 1-4
	Weight of heaviest Part (kg) Weight of heaviest Part (lbs)	201 444
	Shipping Volume (m³) Shipping Volume (ft³)	14,09 497,59
	Total Weight (kg) Total Weight (lbs)	2053,2 4526,6
	Spare Part Guarantee	Lifelong

The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.

* Safety areas as well as free fall height are determined according to a play equipment standard or relevant outdoor fitness standard, depending on the installation. Individual planning is necessary.

Technical Data

Technical changes are reserved.

The following text can also be used for tenders.

Tubes:


Straight and bent steel tubes with a diameter of \varnothing 133 mm (5 1/4") and a wall thickness of 7,1 mm (5/16") with a round cast aluminum post top. Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process.

Bars:

Stainless steel tubes with a diameter of \varnothing 38 mm (1 1/2") and a wall thickness of 5 mm (3/16").

Handles:

The solid handles are made of stainless steel.



1:200

Charlotte-Connector:

Internal fastening system for single rope endings at the arch tubes. The fixing works without hooks or visible ferrules, pre-prepared net segments can easily get installed and still stay exchangeable.

Rope:

The U-Rope® with strand cores and rope core made of galvanised wires has outer strands which are covered with highly abrasion-resistant and highly UV-resistant polyester yarn (not polypropylene). The rope diameter is \varnothing 18 mm (3/4").

Planar Net:

The planar net with a mesh size of at least 250 x 250 mm (9 13/16" x 9 13/16") is permanently localised at the rope crossing points by durable drop-forged aluminium balls (no plastic).