

Spooky Rookies

Wonderwalls.02 Product Specification



Published: August 2021

Wonderwalls.02

Fitted with a wealth of play functions in a reduced space Wonderwalls are specifically aimed at the needs of toddlers and pre-school children. Each equipment design offers a number of play worlds that are interconnected by windows and passages between the three or respectively four walls, which are fanned out around a central post.


As well as space for retreat, children are encouraged to engage in role-playing games using elements such as mud tables, benches,

sand workshops or openings in the walls. Language and social skills are fostered and trained in a playful way.

Toddlers can immerse themselves in the world of wonders and fables at Wonderwalls.02, like pixies. Play elements such as mud tables, hatches in the walls and a sand workshop encourage role play. A hammock made of rubber mats encourages the youngsters to swing or try their first walking and crawling experiences on shaky ground.

90.295.700.2

 Product Family	Spooky Rookies
 Length x Width x Height (m)	5,0 x 2,7 x 1,7
 Length x Width x Height (ft-in)	16-5 x 8-11 x 5-6
 Protective Surfacing Area acc. to DIN EN 1176 (m)	8,0 x 5,7
 Protective Surfacing Area acc. to ASTM/CSA (m)	8,7 x 6,4
 Protective Surfacing Area acc. to ASTM/CSA (ft-in)	28-5 x 20-11
 Fall Height acc. to EN 1176 (m)	1,26
 Fall Height acc. to ASTM/CSA (ft-in)	4-2
 Age	3
 Minimum Space required acc. to DIN EN 1176 (m ²)	30,1
 Minimum Space required acc. to ASTM 1487 (ft ²)	402,9
 Number of Foundations	6
 Concrete Volume C20/C25 (m ³)	1,2
 Number of skilled Installers required	2
 Installation Time without Foundation	8 hours
 Dimensions of largest Part (m)	1,5 x 1,2
 Weight of heaviest Part (kg)	40
 Shipping Volume (m ³)	On request
 Total Weight (kg)	On request
 Spare Part Guarantee	Lifelong



Technical Data

Technical changes are reserved. The following text can also be used for tenders.

Included Products:

- Revolving Flaps
- Ramp
- Sand Slide
- Sand Crane
- Rubber Hammock

Posts:

The steel posts with a diameter of Ø 133 mm (5 ¼") are thermally galvanised to protect against corrosion or, if desired, can be powder-coated in colour using a solvent-free epoxy/ polyester/ process. They are also sealed watertight with rounded aluminium caps.

Tubes:

The Steel tubes with a diameter of Ø 60,3 mm (2 ¾") and a wall thickness of 2,9 mm (1/8") are thermally galvanised to protect against corrosion and powder-coated in colour using a solvent-free epoxy/polyester/process. They are also watertight closed with rounded aluminium caps.

Terranos Clamps:

For height-adjustable connection of the ropes to the steel posts the two-part Terranos® aluminium clamps are used in conjunction with shackle connections.

HDPE-Panels:

Wall, play and design elements are made of solid-coloured and grained HDPE panels with a thickness of 19 mm (¾") and form milled. All edges are rounded off and the walls are connected to the pipes with cast aluminium panel clamps.

Ropes:

The U-Rope® with strand cores and rope core made of galvanised wires has outer strands which are covered with highly abrasion-resistant and highly UV-resistant polyester yarn (not polypropylene).

Rubber Mat:

The rubber mat is made of durable and vandal-proof conveyor belt.