Spooky Rookies

Wonderwalls.01 Product Specification



Published: June 2022

Wonderwalls.01

Fitted with a wealth of play functions in a reduced space Wonderwalls are specifically aimed at the needs of toddlers and pre-school children. Each equipment design offers a number of play worlds that are interconnected by windows and passages between the three or respectively four walls, which are fanned out around a central post. As well as space for retreat, children are encouraged to engage in role-playing games using elements such as mud tables, benches, sand workshops or openings in the walls. Language and social skills are fostered and trained in a playful way.

The highlight of Wonderwalls.01 in the design of a tree stump is a passage with rubber membranes connecting two play areas. And anyone looking closely will find a secret opening under the bench.




Wonderwalls.01

90.295.700.1

<i>JU.2JJ./UU.</i> I	
Product Family	Spooky Rookies
Length x Width x Height (m) Length x Width x Height ('-")	2,3 x 2,7 x 1,7 7-7 x 8-11 x 5-4
Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ('')	5,3 x 5,7 6,0 x 6,4 19-7 x 20-11
Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ('-'')	1,21 4-0
○ ○ Age	3
Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	20,95 287,8
Number of Foundations	5
Concrete Volume C20/C25 (m ³)	0,63
Number of skilled Installers required	2
Installation Time without Foundation	8 hours
□ Dimensions of largest Part (m)	1,5 x 1,2
Weight of heaviest Part (kg)	40
Shipping Volume (m³)	On request
ြဲြြဲ Total Weight (kg)	On request
Spare Part Guarantee	Lifelong





The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.

Technical Data

Technical changes are reserved. The following text can also be used for tenders.

Included Products:

Rubber Membrane Curtain

- Puzzle Elements
- Mud Tables
- Rotating Disc

Tubes:

The Steel tubes with a diameter of Ø 60,3 mm (2%) and a wall thickness of 2,9 mm (%) are thermally galvanised to protect against corrosion and powdercoated in colour using a solvent-free epoxy/polyester/process. They are also watertight closed with rounded aluminium caps.

HDPE-Panels:

Wall, play and design elements are made of solid-coloured and grained HDPE panels with a thickness of 19 mm (34'') and form milled. All edges are rounded off and the walls are connected to the pipes with cast aluminium panel clamps.

Rubber Membrane:

The rubber mat strips are made of durable and vandal-proof conveyor belt.