

Published: June 2023

## Terranova.179

# **Product Specification**

This play walls can be equipped with a wide range of different play functions that support the visual, motor and acoustic perception of the children. Of course, they can be used as painting walls, too. Terranova.179 can be driven under by children sitting in wheel-chairs and meet the requirements of a barrier-free groundlevel component in an elegant way.



# Terranova.179

### 96.180.179

⊕ (3)	7 Product Family	Terranos & Terranova
	Length × Width × Height (m) Length × Width × Height ('-")	5,7 × 0,5 × 2,7 18-7 × 1-8 × 8-11
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ('-")	8,8 × 3,3 9,4 × 3,9 30-10 × 12-9
0 0	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ('-")	-
A C	Age	3
[000]	Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	25,9 357,2
$\Diamond \Diamond \langle$	Number of Foundations	4
• • •	Concrete Volume C20/C25 (m³) Concrete Volume C20/C25 (ft³)	2,8 100
	Number of skilled Installers required	2
	Installation Time without Foundation	2,5 hours
K 7	Dimensions of largest Part (m) Dimensions of largest Part ('-")	3,7 × 0,6 × 0,2 12-2 × 1-10 × 0-6
	Weight of heaviest Part (kg) Weight of heaviest Part (lbs)	82 181
	Shipping Volume (m³) Shipping Volume (ft³)	3,56 125
	Total Weight (kg) Total Weight (lbs)	570 1300
	Spare Part Guarantee	Lifelong





Technical changes are reserved.

The following text can also be used for tenders.

## Play Inserts:

Like our wall panels, our play inserts are made of colored HDPE panels, nominal thickness 19 mm (3/4"). Thematically different inserts, such as mechanical inserts or percussion music instruments, can be used. You can choose 8 out of 35 different inserts in two sizes. Some of them can be played from both sides.

#### Panels:

HPL-panels, colored, thickness 18 mm (11/16"). Connected to steel pipes and posts with Terranos $^\circ$ - clamps and panel connectors.

#### Terranos®-Clamps:

Two-part cast aluminum connecting clamps for the height-adjustable connection of rope elements or steel pipes to Terranos®- steel posts. Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process.

## Terranova Posts:

Terranova steel posts  $\varnothing$  133 mm (5 ¼"), wall thickness 5 - 10 mm (3/16" - 3/8"), bent in a little bow (r=9000 mm), with a round cast aluminum post top. Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process.



