

Published: December 2021

Over Easy

Urban Design Playpoints are climbers or rockers or twisters. They are Playpoints first and foremost, but they are also very nice pieces of public design, and they are sculptural. All URBAN DESIGN Playpoints are high-end engineered units made from high-quality materials like stainless steel with a brushed finish, powder coated

recycled aluminum connectors, high density polyethylene (HDPE) panels and bearings for maximum safety and durability.

This Over Easy gives you the necessary swing. Whether playing with friends or rocking gently back and forth on your own. Also for small playground fans this wobble platform is a great alternative.



Over Easy

	
90.260.151	
Product Family	Urban Design
Length x Width x Height (m) Length x Width x Height ('-'')	1,0 x 1,0 x 0,7 3-3 x 3-3 x 2-1
Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA('-")	4,0 x 4,0 4,7 x 4,7 15-3 x 15-3
Fall Height acc. to ASTM/CSA ('-")	0,42 1-5
○ Age	2-5
Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	12.5 183
Number of Foundations	1
Concrete Volume C20/C25 (ft³)	24.7
Number of skilled Installers required	2
Installation Time without Foundation	2 hours
Dimensions of largest Part ('-'')	3-3 x 3-3 x 3-3
Weight of heaviest Part (lbs)	On request
Shipping Volume (ft³)	35.3
Total Weight (lbs)	440.9
Spare Part Guarantee	Lifelong






Technical changes are reserved. The following text can also be used for tenders.


Base Plate:

The base plate made of stainless steel and HDPE has a diameter of Ø 3'-3" and is framed by welded stainless steel tubes with a diameter of 2 %" and a wall thickness of %".

Stand

The fully encapsulated rubber bearing is firmly integrated in the stainless steel foundation tube.





Scale 1:100

Covering:

The non-skid HDPE plates with a thickness of $\frac{3}{4}$ " are screwed flat on the base plate. The Frameworx® aluminum ball with a diameter of Ø 9 $\frac{13}{6}$ " is sandblasted and powder-coated in color using a solvent-free epoxy-polyester process. It is also securely closed with a durable EPDM cap.